

# SPECIFICATION

Electronic Version 1.2.8

Stylesheet Version 1.0

## Method and Apparatus for Monitoring Electrical Usage

### Field of the Invention

[0001] The present invention relates generally to a system for monitoring electrical usage. More particularly to a system which collects electricity usage information and transmits the information to a central location for analysis.

### Background of Invention

[0002] This invention relates generally to electrical distribution systems and more particularly to a computer-based method and system for installing sub-metering equipments and analyzing energy data.

[0003] Energy auditing is a primary method of collecting and analyzing electrical usage data for electricity utility savings. However, an energy auditing system consists the following components and services: current transformers, electrical meters, wires, computer software, communication devices, a computer, installation and dedicated monitoring personnel. Many existing electrical distribution systems without energy auditing environment are not designed for easily retrofitting such system.

[0004] Therefore, it would be desirable and economical to provide an electricity utility user with an energy auditing retrofit bundle which contains complete hardware, material, computer software user interface, installation instruction and an optional computer.

### Summary of Invention

[0005] In an exemplary embodiment of the present invention, a system for monitoring electricity usage is provided. The system includes a monitoring device having a meter connected to a current transformer and a communications device. The communications device allows transmission of electrical usage information to a server. The data is communicated to the server where it is stored and analyzed to create reports such as demand profile and billing verification. In an alternate embodiment, the server also uses the electrical usage information to determine a new demand profile that results in lower electrical costs for the facility.

[0006] Additional objects, advantages and novel features of the invention will be set forth in part in the description which follows, and in part will become apparent to those skilled in the art upon examination of the following or may be learned by practice of the invention. The objects and advantages of the invention may be realized and attained by means of instrumentalities and combinations particularly pointed out in the appended claims.

### Brief Description of Drawings

[0007] Fig 1 is a perspective view illustrating a facility using a retrofitable power monitoring system;

[0008] Fig 2 is a front view of a monitoring device used in the system of Fig 1;

[0009] Fig 3 is a demand graph report generated by the system of Fig 1;

[0010] Fig 4 is a demand statistics report generated by the system of Fig 1;

[0011] Fig 5 is a bill verification report generated by the system of Fig 1;

[0012] Fig 6 is a flowchart describing the process of determining a new demand profile.

### Detailed Description

[0013] Industrial manufacturing facilities such as those that manufacture goods, or process materials, often utilize complex electrical distribution systems in their operations. Such a distribution system 10 is shown in Figure 1, the electrical power

needed by the industrial facility is generated at a power generation plant 12. High voltage electricity is delivered via transmission and distribution grid 14. The system also includes one or more transformers 15 which step down the high voltage electricity to lower voltages that can be used by the manufacturing facility 16. After the last transformer 15, a low voltage line 17 delivers the electricity to the service entrance 18 of the manufacturing facility 16. Usually, in medium to large facilities, three-phase electrical power is delivered for use. In light manufacturing and residential applications only a single phase of electrical power may be delivered.

[0014] Typically, a circuit breaker 20 will be located at the service entrance 18. The circuit breaker may be any suitable industrial circuit breaker such as an air circuit breaker mounted in switchgear. The service entrance circuit breaker 20 serves as a switch for disconnecting the facility 16 from the electrical distribution grid 14.

[0015] A busway or cable 22 exits the service entrance circuit breaker 20 and delivers the electrical power to the various distribution subsystems within the facility. Usually these system include one or more panelboards 24 which contain banks of circuit breakers (not shown) that divide the electrical power into a number of circuits. The circuit breakers in the panelboards isolate the individual circuits, allowing for example, a circuit on one machine to be disconnected without effecting the remainder of the building.

[0016] As will be described in more detail herein, a monitoring device 23 is also connected to the service entrance circuit breaker 20. The monitoring device 23 collects information on electrical usage for the building. In the preferred embodiment, the monitoring device is connected to a power management and control system 42.

[0017] In manufacturing facilities utilizing large industrial motors, at least one of the circuits 26 will deliver electrical power to a motor control center 25. As will be described in more detail herein, the motor control center 25 has a plurality of sections. These sections contain a number of individual units which further divide the electrical power into further circuits and are used to control and monitor the

performance of the industrial motor 34 associated with a particular circuit. After exiting the motor control center unit 30, the electrical power is delivered by a cable or busway 32 to a local control device 35 which further refines the control or performance of the industrial motor 34. The local control device 35 could for example, be as simple as a contactor, or a more complex device such as motor soft starter. The industrial motor 34 drives a manufacturing process 36 such as a conveyor or a mixer.

[0018] Manufacturing operations consume large amounts of electrical power. To reduce costs and gain more efficiency out of their facility, a power management and control system 42 may be used. To monitor the operation of the facility, the monitoring system 42 includes a server 43 preferably located in a central control room 40. By server it understood that this could include a traditional server such as a desktop computer, or may be a handheld personal digital assistance that receives the data through any communications source (e.g. wirelessly) as described hereafter.

[0019] From the control room 40, communications wiring 38 connects the monitoring system with various monitoring devices 23 throughout the facility 16. The monitoring devices 23 are located in areas where detailed information on the electrical usage is desired. Typical locations would include near the service entrance 20 and the motor control center 25.

[0020] The three phase electrical power is brought to the the monitoring device 23 by a cable 21. Each electrical phase of the cable 21A, 21B, 21C is connected with a current transformer 48, 50 ,52 respectively. In the preferred embodiment, the transformer is a split type transformer that allows the current transformer to be installed as part of a retrofit installation addition the monitoring system without disrupting the electrical service to the facility. The current transformers provide a signal indicative the magnitude of electrical current to a meter 44. The meter receives the signal and calculates various electrical usage parameters such as demand and maximum current. These parameters are stored and periodically transmitted by a communications device 46, such as a RS232-485 converter. The

signal is transmitted over communications wiring 38 to the server 43 in the central control room 40. While the communications link is shown here as a wire 38, this communication can take place over any suitable medium, such as infrared, radio, cellular telephone. The communications may also take Ethernet network or the internet. It should be noted that while the communications device 46 is shown as a separate device, it may also be integral with the meter.

[0021] The electrical usage information is stored in a database on the server 43 for additional analysis. Upon request of the system user, the data is analyzed and various reports can be generated as shown in Figures 3, 4, & 5. These reports allow the user to determine how efficiently the facility is using electricity to minimize the associated costs.

[0022] Since electrical usage is not constant throughout the day or throughout the week, a demand graph report 53 is generated as is shown in Figure 3. The demand report 53 includes a weekly demand profile 54 and a daily demand profile 56 which show which days and weeks generate the maximum demand. These reports are important to the user since the electrical utilities use an electrical usage cost profile to charge different rates depending on the day of the week, and the time of day during which the energy is used. Thus the facility can realize tremendous savings in electrical costs by timing their peak electrical usage during the time periods with the lowest rates.

[0023] Figure 4 depicts the demand statistics report 58 which shows the electrical usage parameters 60 for various time and date ranges 62. Typical electrical parameters 60 reported include peak, average and minimum demand, daily averages and interval peaks.

[0024] The power management system also provides a bill verification report 64 which takes the electrical parameters 66 and electrical usage profile to determine the costs associated with the electrical usage of the facility during On-peak 68, Mid-peak 70 and Off-peak 72 time periods. Thus the user can determine the actual charges for a given period of time to compare and verify the electricity bill sent by the electric utility company.

[0025] In an alternate embodiment, the various report creation functionality is performed with in the meter and the report is transmitted by the communications device to the server for review by the system user. It is contemplated that the report information would be transmitted used using any proprietary or more preferably a industry standard protocol (e.g. html). As described herein above, the server could be a handheld personal digital assistant which retrieves the data directly from the communications device (e.g. radio or optically).

[0026] A process for minimizing electrical costs is illustrated in Figure 6. The current is monitored 74 using a device such as a current transformer as described herein above. Electrical parameters are calculated 76 from the monitored current and transmitted 78 to a server. The server stores 80 the electrical usage parameters. The stored usage parameters are analyzed 82 to generate 84 a demand profile which is indicative of the electrical demand over the course of a desired amount of time. A report 86 of the demand profile may be generated.

[0027] To better optimize the use of electricity by the facility, the demand profile is compared 88 against the electrical usage cost profile. The two profiles are compared to determine 90 which demand peaks are associated with the higher cost periods. Once the high cost demand peaks are determined, a recommended demand profile is generated 92 to lower the electrical costs of the facility. The recommend demand profile will typically move high demand peaks into lower cost time periods, for example, turning the air conditioning off during the day, or starting process motors early in the morning.

[0028] Alternatively, the optimization process and iterative analysis which automatically adjusts the energy usage of the facility. Various subsystems could be classified as discretionary or critical with the monitoring system bringing various systems on and off line in order to minimize the cost of electricity.

[0029] While the invention has been described with reference to a preferred embodiment, it will be understood by those skilled in the art that various changes may be made and equivalents may be substituted for elements thereof without departing from the scope of the invention. In addition, many modifications may be

made to adapt a particular situation or material to the teachings of the invention without departing from the essential scope thereof. Therefore, it is intended that the invention not be limited to the particular embodiment disclosed as the best mode contemplated for carrying out this invention, but that the invention will include all embodiments falling within the scope of the appended claims.

100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000